

Specification

BILT-PLATES® 156

August 24, 2001

RTV Product Code: 08556

Composition: Hydrated aluminum silicate, kaolin

Physical State: Cream powder

<u>Specification</u> <u>Test Method</u>

*Fineness, retained on 325 mesh 0.06% maximum T-938

*Moisture Content 2.0% maximum T-936

GENERAL INFORMATION

Typical values not routinely measured or reported on the Certificate of Analysis.

Brightness 76

Density at 25°C 2.62 Mg/m³

Einlehner Abrasion, 10% Slurry

at 174,000 Revolutions

20 Mg/m²

Hegman Fineness, 3 lbs/gal 4.0

Loss on Ignition 13.3%

Oil Absorption, Rub-Out 41

*Certified Property

Uses - In coatings such as primers, alkyd flats, and latex paints. Filler and extender for polymers and elastomers.

Standard Container - 50 pound paper bag

The information presented herein, while not guaranteed, was prepared by technical personnel and, to the best of our knowledge and belief, is true and accurate as of the date hereof. No warranty, representation or guarantee, express or implied, is made regarding accuracy, performance, stability, reliability or use. This information is not intended to be all –inclusive, because the manner and conditions of use, handling, storage and other factors may involve other or additional safety or performance considerations. The user is responsible for determining the suitability of any material for a specific precautions as may be required. Vanderbilt Minerals, LLC does not warrant the results to be obtained in using any material, and disclaims all liability with respect to the use, handling or further processing of any such material. No suggestion for use is intended as, and nothing herein shall be construed as, a recommendation to infringe any existing patent or to violate any federal, state or local law or regulation.