

## Product Specifications

### SABO<sup>®</sup> STAB UV 62

#### COMPOSITION

Chemical name	Butanedioic acid, 1,4-dimethyl ester, polymer with 4-hydroxy-2,2,6,6-tetramethyl-1-piperidineethanol
CAS number	65447-77-0

#### CRITERIA TESTED REGULARLY AND REPORTED ON C.O.A.

		<u>Sabo test method</u>
Appearance at 20°C	Colorless to light yellowish beads	S62.1
Molecular weight	3100-3400	S62.5
Solution transmission (10% in toluene)	Min. 97% (425 nm)	S62.4
Volatiles	Max. 0.5%	S62.2

#### OTHER CRITERIA TESTED RANDOMLY

Ash	Max. 0.1%
Bead dimensions	Around 2.5 mm
Softening range	50-70°C

Plastic Additives

The following supersedes Buyer's Documents. Sabo makes no representation or warranty, express or implied, including of merchantability or fitness for a particular purpose. No statements herein are to be construed as inducements to infringe any relevant patent. Under no circumstances shall Sabo be liable for incidental, consequential or indirect damages for alleged negligence, breach of warranty, strict liability, tort or contract arising in connection with the product(s). Buyer's sole remedy and Sabo's sole liability for any claims shall be Buyer's purchase price. Data and results are based on controlled or lab work and must be confirmed by Buyer by testing for its intended conditions of use. The product(s) has not been tested for, and is therefore not recommended for, uses for which prolonged contact with mucous membranes, abraded skin, or blood is intended; or for uses for which implantation within the human body is intended.