

Specification

VAN GEL® B Magnesium Aluminum Silicate

July 27, 2023

Product Code: 50140

Composition: Magnesium aluminum silicate, smectite

Physical State: Off-white granules

SPECIFICATION	TEST METHOD

*Moisture Content 8.0% maximum T-684

*Viscosity, Brookfield 300 - 900 cps T-678

#3 spindle at 60 rpm, 4% dispersion

GENERAL INFORMATION

Typical values not routinely measured or reported on the Certificate of Analysis.

pH, 4% Dispersion 9.0

Storage - Store under dry conditions

Re-inspection interval: 5 years

Industrial grades of VAN GEL® Magnesium Aluminum Silicate, including VAN GEL B, are intended for industrial use only. These products are not intended for other uses, such as for pharmaceutical or cosmetic use.

VAN GEL is a registered trademark of Vanderbilt Minerals, LLC.

The information presented herein, while not guaranteed, was prepared by technical personnel and, to the best of our knowledge and belief, is true and accurate as of the date hereof. No warranty, representation or guarantee, express or implied, is made regarding accuracy, performance, stability, reliability or use. This information is not intended to be all—inclusive, because the manner and conditions of use, handling, storage and other factors may involve other or additional safety or performance considerations. The user is responsible for determining the suitability of any material for a specific purpose and for adopting such safety precautions as may be required. Vanderbilt Minerals, LLC does not warrant the results to be obtained in using any material, and disclaims all liability with respect to the use, handling or further processing of any such material. No suggestion for use is intended as, and nothing herein shall be construed as, a recommendation to infringe any existing patent or to violate any federal, state or local law or regulation.

^{*}Certified Property