

Specification

VANLUBE[®] RI-ZSN Corrosion Inhibitor

October 8, 2012

RTV Product Code: 50775 Composition: Zinc dinonylnaphthalene sulfonate Physical State: Dark brown liquid

	Specification	Test Method
*Zinc Content	2.5-3.0%	SH/T0390-1992
*Moisture	1.8% maximum	ASTM D95
*Sulfonate	40.0-42.0%	ASTM D3049

GENERAL INFORMATION

Typical values not routinely measured or reported on the Certificate of Analysis.

Density at 15.6°C	971 Kg/m ³
Flash Point, COC	160°C minimum
Viscosity at 100°C	32 mm²/s

*Certified Property

Uses - Corrosion inhibitor for petroleum products.

Vanlube is a (registered) trademark of R.T. Vanderbilt Holding Company, Inc. or its respective wholly owned subsidiaries

The information presented herein, while not guaranteed, was prepared by technical personnel and, to the best of our knowledge and belief, is true and accurate as of the date hereof. No warranty, representation or guarantee, express or implied, is made regarding accuracy, performance, stability, reliability or use. This information is not intended to be all –inclusive, because the manner and conditions of use, handling, storage and other factors may involve other or additional safety or performance considerations. The user is responsible for determining the suitability of any material for a specific purpose and for adopting such safety precautions as may be required. Vanderbilt Chemicals, LLC does not warrant the results to be obtained in using any material, and disclaims all liability with respect to the use, handling of further processing of any such material. No suggestion for use is intended as, and nothing herein shall be construed as, a recommendation to infringe any existing patent or to violate any federal, state or local law or regulation.