

# Sales Specification

## Vistalon™ 706

### Ethylene Propylene Copolymer Rubber

#### Product Description

Vistalon 706 rubber is a medium Mooney, medium ethylene copolymer designed for use in the production of belts. This product is sold in dense bales.

Physical	Target	Minimum	Maximum	Unit	Test Based On
Antioxidant content, non staining	0.10	0.05	0.15	wt%	ExxonMobil Method
Vanadium	--	--	25	wtppm	ExxonMobil Method
Mooney Viscosity <sup>1</sup> (ML 1+4, 125°C)	42	37	47	MU	ASTM D1646 (mod)
Volatiles	--	--	1.00	%	ISO 248 (mod)
Ethylene Content	65.0	63.0	67.0	wt%	ASTM D3900A

#### Notes

<sup>1</sup> Radial cavity dies, polymer remassed at 145±10°C.

For additional technical, sales and order assistance:

Worldwide and the Americas  
ExxonMobil Chemical Company  
13501 Katy Freeway  
Houston, TX 77079-1398  
USA  
1-281-870-6050

Asia Pacific  
ExxonMobil Chemical Asia Pacific  
1 HarbourFront Place  
#06-00 HarbourFront Tower One  
Singapore 098633  
+86-21-24173999

Europe, Middle East and Africa  
ExxonMobil Chemical Europe  
Hermeslaan 2  
1831 Machelen, Belgium  
420-239-016-274

©2012 ExxonMobil. ExxonMobil, the ExxonMobil logo, the interlocking "X" device and other product or service names used herein are trademarks of ExxonMobil, unless indicated otherwise. This document may not be distributed, displayed, copied or altered without ExxonMobil's prior written authorization. To the extent ExxonMobil authorizes distributing, displaying and/or copying of this document, the user may do so only if the document is unaltered and complete, including all of its headers, footers, disclaimers and other information. You may not copy this document to or reproduce it in whole or in part on a website. ExxonMobil does not guarantee the typical (or other) values. Any data included herein is based upon analysis of representative samples and not the actual product shipped. The information in this document relates only to the named product or materials when not in combination with any other product or materials. We based the information on data believed to be reliable on the date compiled, but we do not represent, warrant, or otherwise guarantee, expressly or impliedly, the merchantability, fitness for a particular purpose, freedom from patent infringement, suitability, accuracy, reliability, or completeness of this information or the products, materials or processes described. The user is solely responsible for all determinations regarding any use of material or product and any process in its territories of interest. We expressly disclaim liability for any loss, damage or injury directly or indirectly suffered or incurred as a result of or related to anyone using or relying on any of the information in this document. This document is not an endorsement of any non-ExxonMobil product or process, and we expressly disclaim any contrary implication. The terms "we," "our," "ExxonMobil Chemical" and "ExxonMobil" are each used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliate either directly or indirectly stewarded.